COCO

ARKOSLIGHT

Compacto y poderoso

Nueva generación LED. **154 lm/W** de eficacia lumínica. Un cilindro compacto en aluminio con un **flujo de 1340 lm**.

Libertad de movimientos

Rotación de **360°** e inclinación de **90°**.

COCO

COCO 48V TUNABLE WHITE

Libertad de iluminación

Tres ángulos de apertura **spot** / **medium** / **flood** + versión **Super spot 12°**.
Cubre múltipes necesidades: iluminación de acento, general...

Coco Super Spot

Altamente técnico **(12° apertura de haz de luz)**.
LED y lentes de alta calidad cuidadosamente seleccionadas.
Mantiene un flujo uniforme y un marcado confort visual.

Opción DIM on board

Integración perfecta para sistemas 48V.
Permite regular de **0** a **100** la intensidad de cada luminaria de manera independiente.

Accesorios

Dispone de diferentes accesorios:
anti-glare honeycomb y
anti-glare screen, que reducen
el deslumbramiento y favorecen el
confort visual.

COCO ANTI-GLARE SCREEN

COCO ANTI-GLARE
HONEYCOMB LOUVER

Linear Filter

Transforma el haz de luz circular en una **forma lineal**.
Ideal para aplicaciones donde se necesita una distribución precisa y lineal de la luz.

MAGNETIC 24V COCO

DEFINIDO



CIRCULAR RECTANGULAR POLIGONAL

DIFUMINADO

CIRCULAR RECTANGULAR POLIGONAL

CUSTOM

OPCIÓN GOBO

Coco Shaper

Crea escenografías únicas proyectando el contorno geométrico deseado: circunferencias, polígonos cuadriláteros o triangulares.

8:20 h · 3700 K

12:00 h · 5000 K

17:00 h · 2700 K

Tunable white

Versión disponible para Coco 48V. Muy apreciado en ambientes domésticos, hostelería, oficina, etc.

COCO
ESPECIFICACIONES TÉCNICAS

MAGNETIC 24V COCO

		P	CCT	Beam	I	Flux	LOR
MAGNETIC 24V COCO	A499-00-10- | WT | NT |	8,7W	2700K	20°	500mA	1200 lm	87%
	A499-00-11- | WT | NT |	8,7W	3000K	20°	500mA	1250 lm	87%
	A499-00-12- | WT | NT |	8,7W	4000K	20°	500mA	1340 lm	87%
	A499-00-20- | WT | NT |	8,7W	2700K	34°	500mA	1200 lm	89%
	A499-00-21- | WT | NT |	8,7W	3000K	34°	500mA	1250 lm	89%
	A499-00-22- | WT | NT |	8,7W	4000K	34°	500mA	1340 lm	89%
	A499-00-30- | WT | NT |	8,7W	2700K	48°	500mA	1200 lm	86%
	A499-00-31- | WT | NT |	8,7W	3000K	48°	500mA	1250 lm	86%
	A499-00-32- | WT | NT |	8,7W	4000K	48°	500mA	1340 lm	86%

24 V | III **IP**20 | CRI>90 | L80B10 > 66.000 h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 20° / 34° / 48°

		P	CCT	Beam	I	Flux	LOR
MAGNETIC 24V COCO **Super Spot**	A499-00-00- | WT | NT |	6W	2700K	12°	500mA	750 lm	66%
	A499-00-01- | WT | NT |	6W	3000K	12°	500mA	800 lm	66%
	A499-00-02- | WT | NT |	6W	4000K	12°	500mA	850 lm	66%

24 V | III **IP**20 | CRI>90 | L80B10 > 55.000 h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 12°

OPTIONAL ACCESSORIES

COCO **Anti-glare Honeycomb Louver****

A498-90-00- | WT | NT |

COCO **Linear Filter****

A498-90-02- | WT | NT |

SUITABLE FOR BEAM ≤ 34°

COCO **Anti-glare Screen****

A498-90-01- | WT | NT |

COCO **High Chromatic Led**** » 281

NOT SOLD SEPARATELY

TRIMLESS TOOL **D16 X D34mm**

A478-00-00



MAGNETIC 24V CONNECTOR A435-01-00 | W | N |

* MANDATORY FOR INSTALLATION

III **IP**20 | Ø16





INCLUDED EXTRA COVER FOR RECESSED VERSION



		P	V	D (A x B x C)
24V POWER SUPPLY	0434-01-37	60W	24V	180 x 52 x 30mm
	0433-10-22	100W	24V	295 x 43 x 30mm

220 240 V~ | MUST BE PLACED ON REMOTE



24V DIMMER	0433-01-32	DALI / Push	24V	181 x 42 x 20mm
	0433-01-33	CASAMBI	24V	172 x 42 x 20mm
	0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V | MUST BE PLACED ON REMOTE
OTHER DIM OPTIONS PLEASE CONSULT

DROP VOLTAGE » 287



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC/PMMA |

PLEASE CONSULT »

OTHER CCT OPTIONS PLEASE CONSULT
** AFFECTS THE LIGHTING PARAMETERS

COCO 48V

COCO 48V	+RE	P	CCT	Beam	I	Flux	LOR
A498-0- ⓪ -10- | WT | NT | WTW | NTW |	-S	8,7W	2700K	20°	500mA	1200 lm	87%
A498-0- ⓪ -11- | WT | NT | WTW | NTW |	-S	8,7W	3000K	20°	500mA	1250 lm	87%
A498-0- ⓪ -12- | WT | NT | WTW | NTW |	-S	8,7W	4000K	20°	500mA	1340 lm	87%
A498-0- ⓪ -20- | WT | NT | WTW | NTW |	-S	8,7W	2700K	34°	500mA	1200 lm	89%
A498-0- ⓪ -21- | WT | NT | WTW | NTW |	-S	8,7W	3000K	34°	500mA	1250 lm	89%
A498-0- ⓪ -22- | WT | NT | WTW | NTW |	-S	8,7W	4000K	34°	500mA	1340 lm	89%
A498-0- ⓪ -30- | WT | NT | WTW | NTW |	-S	8,7W	2700K	48°	500mA	1200 lm	86%
A498-0- ⓪ -31- | WT | NT | WTW | NTW |	-S	8,7W	3000K	48°	500mA	1250 lm	86%
A498-0- ⓪ -32- | WT | NT | WTW | NTW |	-S	8,7W	4000K	48°	500mA	1340 lm	86%

48 V | IP20 | CRI>90 | L80B10 >66.000 h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360° | 90° | 20° / 34° / 48°

OPTIONAL ACCESSORIES

AFFECT THE LIGHTING PARAMETERS

COCO Anti-glare Honeycomb Louver

A498-90-00- | WT | NT |

COCO 48V Super Spot	+RE	P	CCT	Beam	I	Flux	LOR
A498-0- ⓪ -00- | WT | NT | WTW | NTW |	-S	6W	2700K	12°	500mA	750 lm	66%
A498-0- ⓪ -01- | WT | NT | WTW | NTW |	-S	6W	3000K	12°	500mA	800 lm	66%
A498-0- ⓪ -02- | WT | NT | WTW | NTW |	-S	6W	4000K	12°	500mA	850 lm	66%

48 V | IP20 | CRI>90 | L80B10 >55.000 h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360° | 90° | 12°

COCO Anti-glare Screen

A498-90-01- | WT | NT |

COCO 48V Tunable White	+RE	P	CCT	Beam	I	Flux	LOR
A498-12-18- | WT | NT | WTW | NTW |	-S	8,5W	2700-5000K	28°	500mA	1010 lm	85%
A498-12-28- | WT | NT | WTW | NTW |	-S	8,5W	2700-5000K	42°	500mA	1010 lm	87%
A498-12-38- | WT | NT | WTW | NTW |	-S	8,5W	2700-5000K	54°	500mA	1010 lm	84%

48 V | IP20 | CRI>90 | L80B10 >55.000 h

MacAdam Step 3 | DALI* | INCL | TRACK 48V | 360° | 90° | 28° / 42° / 54°

COCO Linear Filter

A498-90-02- | WT | NT |

SIUTABLE FOR BEAM ≤ 34°

COCO High Chromatic Led

» 281

NOT SOLD SEPARATELY

⓪	*OPTIONS
1	No DIM
2	DIM DALI
7	DIM ON BOARD

OTHER DIM OPTIONS PLEASE CONSULT

+RE	REF. ENDING	EXAMPLE
Ø	Track 48V	A4980110WT
-S	Track 48V Short	A4980110WT-S

FINISHING	Lamp	Adaptor
WT	WT ☐	N ■
NT	NT ■	N ■
WTW	WT ☐	W ☐
NTW	NT ■	W ☐

COCO 48V



VISIBLE LIMIT

COCO 48V SHORT (-S)



COLOUR | WT ☐ | NT ■ | MATERIAL | AL | PC/PMMA | PLEASE CONSULT »

OTHER CCT PLEASE CONSULT

+RE >> THE PRODUCTS FOR THE *TRACK 48V SHORT*, ADD "**-S**" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

OPTIONAL ACCESSORIES

COCO

COCO SUPER SPOT

COCO ANTI-GLARE HONEYCOMB LOUVER

COCO LINEAR FILTER

COCO ANTI-GLARE SCREEN

FINISHINGS

NT

WT

NTW

WTW

NT

WT

NT SUPER SPOT

WT SUPER SPOT

COCO SHAPER 48V

COCO SHAPER 48V					+RE	P	CCT	Beam	I	Flux	LOR
A519-0-		-00-	NT	NTW	-S	6W	2700K	20º-33º	500mA	650 lm	40-38%
A519-0-		-01-	NT	NTW	-S	6W	3000K	20º-33º	500mA	680 lm	40-38%
A519-0-		-02-	NT	NTW	-S	6W	4000K	20º-33º	500mA	730 lm	40-38%
A519-0-		-10-	NT	NTW	-S	6W	2700K	53º	500mA	650 lm	37%
A519-0-		-11-	NT	NTW	-S	6W	3000K	53º	500mA	680 lm	37%
A519-0-		-12-	NT	NTW	-S	6W	4000K	53º	500mA	730 lm	37%

48 V | III IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360º | 90º | 20º - 33º / 53º

	*OPTIONS
1	No DIM
2	DIM DALI

OTHER DIM OPTIONS
PLEASE CONSULT

+RE	REF. ENDING	EXAMPLE
Ø	Track 48V	A5190110NT
-S	Track 48V Short	A5190110NT-S

FINISHING	Lamp	Adaptor
NT	NT ■	N ■
NTW	NT ■	W □

COCO SHAPER 48V



VISIBLE LIMIT

COCO SHAPER 48V SHORT (-S)



COLOUR | NT ■ | MATERIAL | AL | OPTICAL GLASS | PLEASE CONSULT »

OTHER CCT PLEASE CONSULT
+RE >> THE PRODUCTS FOR THE *TRACK 48V SHORT*, ADD "**-S**" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).
CUSTOM GOBO PLEASE CONSULT

COCO SHAPER RECESSED

		P	CCT	Beam	I	Flux	LOR
COCO SHAPER Recessed	A519-1- ⓘ -00- | NT |	6W	2700K	20º-33º	500mA	650 lm	40-38%
	A519-1- ⓘ -01- | NT |	6W	3000K	20º-33º	500mA	680 lm	40-38%
	A519-1- ⓘ -02- | NT |	6W	4000K	20º-33º	500mA	730 lm	40-38%
	A519-1- ⓘ -10- | NT |	6W	2700K	53º	500mA	650 lm	37%
	A519-1- ⓘ -11- | NT |	6W	3000K	53º	500mA	680 lm	37%
	A519-1- ⓘ -12- | NT |	6W	4000K	53º	500mA	730 lm	37%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | INCL | Ø50 | 360º | 90º | 20º - 33º / 53º

ⓘ	*OPTIONS
1	No DIM
2	DIM DALI

OTHER DIM OPTIONS
PLEASE CONSULT



COLOUR | NT ■ | MATERIAL | AL | OPTICAL GLASS | PLEASE CONSULT »

OTHER CCT PLEASE CONSULT
CUSTOM GOBO PLEASE CONSULT

BEAM & FINISHINGS

53° | NT

20°- 33° | NT

53° | NT

20°- 33° | NT

53° | NTW

20°- 33° | NTW

CO

by ARKOSLIGHT